

## CLAIMS:

1. Error checking circuitry for performing error checks based on mathematical functions comprising:

a data input stage having a data node adapted to receive incoming data to be checked and a plurality of input feedback nodes;

a register having a plurality of data input nodes each data input node being selectable to receive data from the data input stage and a set of output feedback nodes arranged to selectively supply a feedback signal to the data input stage; and

multiplexing circuitry provided in association with the register and the data input stage to selectively connect one of said output feedback nodes to the data input stage and to selectively connect said data node to at least some of said data input nodes such that the signal routes through the error checking circuitry are configurable to successively perform error checks based on different mathematical functions.

2. Error checking circuitry according to claim 1, wherein the register comprises a plurality of delay elements, each capable of holding one bit.

3. Error checking circuitry according to claim 2, wherein the register comprises a first data input node and a plurality of further data input nodes disposed between selected ones of the delay elements.

4. Error checking circuitry according to claim 3, wherein the multiplexing circuitry is arranged to selectively connect an incoming data signal from the input stage and a zero signal to said data input nodes of the register.

5. Error checking circuitry according to any preceding claim, wherein the multiplexing circuitry comprises combinatorial logic for combining the incoming data with a feedback signal from said register.

6. Error checking circuitry according to claim 5, wherein said multiplexing circuitry includes two combinatorial logic stages each comprising an XOR-gate.

7. Error checking circuitry according to claim 6, wherein the multiplexing circuitry includes two multiplexing stages each receiving an input from said combinatorial logic stages.

8. Error checking circuitry according to claim 7, wherein a multiplexor select signal indicating the mathematical function to be used is supplied to both said multiplexing stages.

9. Error checking circuitry according to any preceding claim, wherein the register comprises a number of delay elements sufficient to implement error checking based on a 32-bit CRC generator polynomial.

10. Error checking circuitry according to any preceding claim, wherein the incoming data comprises a digital video data stream.

11. Error checking circuitry according to any of claims 3 to 10, wherein certain ones of said further data input nodes are, in use employed in error checks based on both said 32-bit and 16-bit CRC generator polynomials.

12. A method of checking an incoming bit stream for errors, comprising the steps of:

receiving at an input stage an incoming bit stream;

subsequently disconnecting said feedback signal and connecting another one of said feedback signals to the input stage thereby to perform an error check based on a second, different, mathematical function.

14. Error checking circuitry substantially as described herein with reference to Figure 4.